

Название:	Nickel/alumina nanocomposites by AC electrochemical processing
Авторы:	A.I. Vorobyova , E.A. Outkina , A. A. Khodin
Ключевые слова:	Electrochemical deposition; Anodizing; Porous anodic alumina; Barrier layer; Ni Nanowires
Дата публикации:	2016
Издатель:	Springer Berlin Heidelberg
Библиографическое описание:	A.I. Vorobyova , E.A. Outkina , A. A. Khodin Nickel/alumina nanocomposites by AC electrochemical processing //Applied Physics A. Materials Science & Processing. - Volume 122, N2, 2016, P.109–117

Abstract/Аннотация

Nanowire/pillar composite fabricated by alternating current electrochemical deposition of nickel into/onto thin porous anodic alumina (PAA) is investigated for magnetosensitive medium applications. Magnetization and current transport features of Ni nanowires/porous matrix composite in the current-perpendicular-to-plane mode are considered. Fabrication processing features, SEM characterization results are presented. PAA/Ni nanocomposite with Ni nanoparticles of 15–25 nm characteristic size is formed at initial stages of deposition. Continuous Ni nanowires/nanotubes composites are formed over the whole alumina pores depth after ~10-min deposition. XRD analysis confirms the polycrystalline nature of Ni nanowires with [111] preferential orientation.